

# DETOUREUSES SIOUX



### Performance:

Power: 1.0 hp (0.75 kw)  
 Speed: 18,000 rpm – 25,000 rpm  
 Collet Size: 1/4" – (6 mm)

### 1 HP (0.75 kw) Routers

### Features:

Lockoff Lever Throttle  
 Front Exhaust  
 Interchangeable Base  
 Built-in Speed Control

Model Number	Collet Size	Free Speed	Weight		Height		Maximum Air Consumption		Sound Level
		rpm	lb	kg	In	mm	cfm	l/s	dB(A)
<b>Template Nose</b>									
SRT 10S18N	1/4	18,000	2.1	0.95	9.0	230	30	14	76
SRT 10S18MBN	6 mm	18,000	2.1	0.95	9.0	230	30	14	76
SRT 10S25N	1/4	25,000	2.1	0.95	9.0	230	30	14	76
SRT 10S25MBN	6 mm	25,000	2.1	0.95	9.0	230	30	14	76
<b>3" Base</b>									
SRT 10S18B	1/4	18,000	2.1	0.95	9.0	230	30	14	76
SRT 10S18MB	6 mm	18,000	2.1	0.95	9.0	230	30	14	76
SRT 10S18BB	1/4	18,000	2.6	1.15	8.3	210	30	14	76
SRT 10S25B	1/4	25,000	2.1	0.95	9.0	230	30	14	76
SRT 10S25MB	6 mm	25,000	2.1	0.95	9.0	230	30	14	76
SRT 10S25BB	1/4	25,000	2.6	1.15	8.3	210	30	14	76
<b>Laminated Trimmer</b>									
SRT 10S18LT	1/4	18,000	2.9	1.30	9.3	235	30	14	76
SRT 10S25LT	1/4	25,000	2.9	1.30	9.3	235	30	14	76

Template guides must be ordered separately

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Base/Head Assembly, Collet, Collet Wrenches

### Performance:

Power: 1.5 hp (1.12 kw)  
 Speed: 20,000 rpm  
 Collet Size: 1/4" – 1/2"

### 1.5 HP (1.12 kw) Routers

### Features:

Twist and Finger Throttle  
 4" (102 mm) or 6" (152 mm) Diameter Base  
 Side Exhaust



Model Number	Collet Size	Free Speed	Weight		Height		Base Diameter		Maximum Air Consumption		Sound Level
		rpm	lb	kg	In	mm	In	mm	cfm	l/s	dB(A)
<b>Finger Throttle</b>											
1981F	1/2"	20,000	6.0	2.7	9.8	246	4.0	102	36	18	85
<b>Twist Throttle</b>											
1980A	1/4"	20,000	4.5	2.0	7.6	193	4.0	102	36	18	85
1980	3/8"	20,000	4.5	2.0	7.6	193	4.0	102	36	18	85
RT1981	1/2"	20,000	4.5	2.0	7.6	193	4.0	102	36	18	85
1982A	1/4"	20,000	7.5	3.4	8.3	211	6.0	152	36	18	85
RT1982	3/8"	20,000	7.5	3.4	8.3	211	6.0	152	36	18	85
RT1983	1/2"	20,000	4.8	2.2	8.3	211	6.0	152	36	18	85

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Base & Collet Wrenches

MAJ : 02.08  
 Vérif. : N.P.L  
 Appr. : C . P

Distribution OPINDUS



Matériel conforme à la D.E 89/392/CEE, aux Normes EN292-1 et 2, EN294

OPINDUS : 1, Rue Maurice Audibert 69800 SAINT PRIEST Tél : 04.78.21.73.14 - Fax : 04.78.21.73.01