

VISSEUSES DROITES SERIE LD

Standard Equipment

Vertical hanger

Suspension verticale

Vertikal-Aufhänger

Suspensión vertical

Dispositivo sospensione verticale

Specifications at 90 psi - Caractéristiques à 620 kPa - Technische Daten bezogen auf 620 kPa - Especificaciones a 620 kPa - Caratteristiche a 620 kPa

Options

Ref. LDX2XXRDX-XX-DI

Dual information kit⁽¹⁾

Kit prise d'info⁽¹⁾

2-fach Signal⁽¹⁾

Doble señal⁽¹⁾

Doppia informazione



LD1207RD5-Q4



LD2206RD5-Q4

Straight Screwdrivers
Visseuses Droites
Druckluftdrehschrauber, gerade Ausführung
Atornilladores con Empuñadura Recta
Cacciaviti con Impugnatura Diritta



Adjustable shut-off clutch models — Modèles avec limiteur de couple réglable à coupure d'air — Modelle mit einstellbarer Abschaltkupplung — Modelos con parada automática — Modelli con frizione regolabile con blocco aria

Ref.	mm	rpm	kg	mm	mm	in	1/min
OC LEVER START — DÉM. PAR LEVIER — HEBELSTART — ARRANQUE POR PALANCA — AVVIAMENTO A LEVA							
LD1214RD5-Q4	1.1 - 2.5	1500	0.7	231	17	1/4	460
LD1207RD5-Q4	1.2 - 4.2	800	0.7	231	17	1/4	460
LD2216RD5-Q4	1.8 - 4.5	1550	1.0	272	18	1/4	620
LD2210RD5-Q4	2.4 - 5.9	1000	1.0	272	18	1/4	620
LD2206RD5-Q4	2.1 - 9.8	600	1.0	272	18	1/4	620
LD1202RD5-Q4	1.6 - 10	180	0.8	243	17	1/4	460
LD2203RD5-S6	10 - 15	300	1.1	293	18	3/8	620
OC PUSH START — DEM. PAR POUSSÉE — SCHUBSTART — ARRANQUE POR EMPUJE — AVVIAMENTO A SPINTA							
LD1214RD3-Q4	1.1 - 2.5	1500	0.7	231	17	1/4	460
LD1207RD3-Q4	1.2 - 4.2	800	0.7	231	17	1/4	460
LD2216RD3-Q4	1.8 - 4.5	1550	1.0	272	18	1/4	620
LD2210RD3-Q4	2.4 - 5.9	1000	1.0	272	18	1/4	620
LD2206RD3-Q4	2.1 - 9.8	600	1.0	272	18	1/4	620
LD1202RD3-Q4	1.6 - 10	180	0.8	243	17	1/4	460

Series / Baureihe	Headset	Earplugs	Earplugs
LD12	70 dBA	1/4" BSP	9 mm
LD22	72 dBA	1/4" BSP	13 mm

- (1) For dual information kit, add "-DI" to tool model no. (e.g. LD2216RD5-Q4-DI).
- (1) Pour kit prise d'info: ajouter "-DI" à la référence (exemple LD2216RD5-Q4-DI).
- (1) 2-fach Signal ergänzen Sie die Model-Nr. mit "-DI" (z. B. LD2216RD5-Q4-DI).
- (1) Para doble señal, añadir "-DI" a la referencia (ejemplo LD2216RD5-Q4-DI).
- (1) Per doppia informazione, aggiungere "-DI" al codice del modello (es. LD2216RD5-Q4-DI).

MAJ : 02.08
 Vérif. : N.P.L
 Appr. : C. P

Distribution OPINDUS



Matériel conforme à la D.E 89/392/CEE, aux Normes EN292-1 et 2, EN294

OPINDUS : 1, Rue Maurice Audibert 69800 SAINT PRIEST Tél : 04.78.21.73.14 - Fax : 04.78.21.73.01