

PONCEUSES D'ANGLE SIOUX

RIGHT ANGLE SANDERS



SAS03S122-20



SAS05S232-20



SAS10A182-20



77016 Threaded Arbor



300 Series Collet

Performance:

Power: 0.33 hp (0.25 kw) – 1 hp (.75 kw)
Speed: 12,000 rpm – 23,000 rpm

Features:

Lockoff Lever Throttle
Front, Rear, and Vacuum Exhaust
Comfort Grip

Right Angle Disc Sanders



Model Number	Free Speed		Weight		Length		Air Consumption Free Speed		Sound Level	Spindle Thread
	rpm		lb	kg	in	mm	cfm	l/s	dB(A)	
0.3 hp (.22 kw) – Lever Throttle										
SAS03S122-20	12,000		1.1	.5	5.625	143	11	5.2	82.2	1/4"-20
SAS03S202-20	20,000		1.1	.5	5.625	143	11	5.2	82.9	1/4"-20
0.5 hp (.37 kw) – Lever Throttle										
SAS05S232-20	23,000		1.3	.59	5.625	143	23	10.3	88.6	1/4"-20
1 hp (.75 kw) – Lever Throttle										
SAS10A122-20	12,000		2.15	.98	7.5	190	30	14	84.6	1/4"-20
SAS10A152-20	15,000		2.15	.98	7.5	190	30	14	TBD	1/4"-20
SAS10A182-20	18,000		2.15	.98	7.5	190	30	14	TBD	1/4"-20

General:

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment:

Parts List • Safety and Instruction Manual • Support Handle (1 hp Models) • Spindle Wrenches, 300 Series Collet, 1/4"-20 Threaded Arbor

MAJ : 02.08 Vérif. : N.P.L Appr. : C . P	Distribution OPINDUS	
Matériel conforme à la D.E 89/392/CEE, aux Normes EN292-1 et 2, EN294		
OPINDUS : 1, Rue Maurice Audibert 69800 SAINT PRIEST Tél : 04.78.21.73.14 - Fax : 04.78.21.73.01		

RIGHT ANGLE SANDERS



SAS10S125



SAS10A125



SAS10AX125



1287L



Performance:

Power: 1 hp (0.75 kw)
Speed: 6000 rpm – 12,000 rpm

Features:

Governed & Non-Governed
Lockoff Lever Throttle
Rear Exhaust on SAS Series

Right Angle Sanders

Model Number	Free Speed	Pad Diameter		Weight		Length		Air Consumption Under Load		Air Consumption Free Speed		Sound Level dB(A)	Spindle Thread
	rpm	In	mm	lb	kg	In	mm	cfm	l/s	cfm	l/s		
1 hp (0.75 kw) – Lockoff Lever Throttle – Rear Exhaust													
SAS10S125	12,000	5	125	3.5	1.6	8.3	210	N/A	N/A	35	17	77	3/8 – 24
SAS10A125	12,000	5	125	2.2	1.0	7.75	124	N/A	N/A	35	17	84.1	5/8"-11
SAS10AX125	12,000	5	125	3.2	1.45	11.25	285	N/A	N/A	35	17	83.2	5/8"-11
1 hp (0.75 kw) – Governed Speed Control – Lockoff Lever Throttle													
1287L ¹	6000	7	175	5.9	2.7	11.3	287	35	17	18	8	85	5/8"-11

¹Not CE certified.

General:

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment:

Parts List • Safety and Instruction Manual • Support Handle • Spindle Wrenches • Backing Pad & Nut

MAJ : 02.08
Vérif. : N.P.L
Appr. : C . P

Distribution OPINDUS



Matériel conforme à la D.E 89/392/CEE, aux Normes EN292-1 et 2, EN294

OPINDUS : 1, Rue Maurice Audibert 69800 SAINT PRIEST Tél : 04.78.21.73.14 - Fax : 04.78.21.73.01