

# TARAUDEUSES SIOUX



## Performance:

Power: 1 hp (0.75 kw)  
 Torque: 145 in. lb (16 Nm) – 400 in.  
 lb (45 Nm)  
 Speed: 300 rpm – 1200 rpm

## Features:

Pistol Grip Handle  
 Rapid Reverse

## Capacity:

1/4" in Steel  
 5/16" in Aluminum

## Tappers



Model Number	Chuck Capacity		Maximum Torque		Free Speed rpm	Weight		Length		Air Consumption		Sound Level dB(A)
	in	mm	in lb	Nm		lb	kg	in	mm	cfm	l/s	
<b>1 hp (0.75 kw) – Pistol Grip – Trigger Start</b>												
STP10P3C20	#10-5/16	5-8	400	45	300	2.9	1.3	7.3	185	30	14	80
STP10P3C32	1/4-1/2	6-13	400	45	300	2.9	1.3	7.3	185	30	14	80
<b>1 hp (0.75 kw) – In-line – B12 Taper Spindle</b>												
STP10S12B12			145	16	1200	2.5	1.2	9.5	240	30	14	78
STP10S7B12			220	25	700	2.5	1.2	9.5	240	30	14	78
STP10S5B12			325	37	500	2.5	1.2	9.5	240	30	14	78
STP10S3B12			400	45	300	2.5	1.2	9.5	240	30	14	78

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Comfort Grip • Tapping Chuck (model STP10P3C series)

MAJ : 02.08 Vérif. : N.P.L Appr. : C . P	<b>Distribution OPINDUS</b>	
Matériel conforme à la D.E 89/392/CEE, aux Normes EN292-1 et 2, EN294		
<b>OPINDUS</b> : 1, Rue Maurice Audibert 69800 SAINT PRIEST Tél : 04.78.21.73.14 - Fax : 04.78.21.73.01		